



Hanwha TotalEnergies Petrochemical Co Ltd
103 Dokgot 2-ro Daesan-eup
Seosan-si, Chungcheongnam-do 31900 Republic of Korea



BI45(+)

Polypropylene (PP), pellets, modified

+ - May represented by one, two, three, four and five number(s) and/or letter(s) to denote a specific color code.

可燃性	值	测试方法
UL 阻燃等级		
1.0 mm, ALL	HB	UL 94
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.0 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
电气性能	值	测试方法
热丝引燃 (HWI) (1.5 mm)	PLC 2	UL 746A
高电弧燃烧指数(HAI) (1.5 mm)	PLC 0	UL 746A
热性能	值	测试方法
RTI Elec		UL 746B
1.0 mm	65.0 °C	
1.5 mm	125 °C	
3.0 mm	125 °C	
RTI Imp		UL 746B
1.0 mm	65.0 °C	
1.5 mm	125 °C	
3.0 mm	125 °C	
RTI		UL 746B
1.0 mm	65.0 °C	
1.5 mm	125 °C	
3.0 mm	125 °C	