



EASTMAN CHEMICAL CO PERFORMANCE PLASTICS
PO BOX 1969
KINGSPORT, TN 37662-1963 United States



TRITAN: TX2001, Renew TX2001-25, Renew TX2001-50

Co-Polyester, pellets

NOTE - May be followed by A, C, E or G.

| 可燃性 | 值 | 测试方法 |
|--------------|---------|----------------------|
| UL 阻燃等级 | | |
| 1.5 mm, ALL | HB | UL 94 |
| 3.0 mm, ALL | HB | UL 94 |
| 3.0 mm, ALL | HB40 | IEC 60695-11-10, -20 |
| 1.5 mm, ALL | HB75 | IEC 60695-11-10, -20 |
| 电气性能 | 值 | 测试方法 |
| 热丝引燃 (HWI) | | UL 746A |
| 1.5 mm | PLC 4 | |
| 3.0 mm | PLC 3 | |
| 高电弧燃烧指数(HAI) | | UL 746A |
| 1.5 mm | PLC 0 | |
| 3.0 mm | PLC 0 | |
| 热性能 | 值 | 测试方法 |
| RTI Elec | | UL 746B |
| 1.5 mm | 95.0 °C | |
| 3.0 mm | 95.0 °C | |
| RTI Imp | | UL 746B |
| 1.5 mm | 95.0 °C | |
| 3.0 mm | 95.0 °C | |
| RTI | | UL 746B |
| 1.5 mm | 95.0 °C | |
| 3.0 mm | 95.0 °C | |