



Component - Plastics

File Number: E162823

FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV
201 TUNG HWA N RD
TAIPEI, 105 Taiwan



TAIRILOY: AC3300

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), pellets

Flammability	Value	Test Method
Flame Rating		UL 94
1.2 mm, ALL	V-0	IEC 60695-11-10, -20
1.6 mm, ALL	V-0, 5VB	
1.8 to 2.0 mm, ALL	V-0, 5VB	
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.2 mm	PLC 3	
1.6 mm	PLC 1	
1.8 to 2.0 mm	PLC 1	
High Amp Arc Ignition (HAI)		UL 746
1.2 mm	PLC 0	
1.6 mm	PLC 0	
1.8 to 2.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 0	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 2	UL 746
Arc Resistance	PLC 6	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746
1.2 mm	60.0 °C	
1.6 mm	60.0 °C	
1.8 to 2.0 mm	60.0 °C	
RTI Imp		UL 746
1.2 mm	60.0 °C	
1.6 mm	60.0 °C	
1.8 to 2.0 mm	60.0 °C	
RTI Str		UL 746
1.2 mm	60.0 °C	
1.6 mm	60.0 °C	
1.8 to 2.0 mm	60.0 °C	