



<b>Grade</b>	FL7200
<b>Product</b>	HDPE

#### General Information

#### Key Features

- FL7200 is a bimodal high density polyethylene copolymer which has a broad molecular weight distribution.
- The design of the product gives an unique characteristic of easy extrusion and high melt strength with excellent physical properties which makes it suitable for use in very thin film with excellent strength and rigidity.

#### Applications

- Thin film for bag on roll, grocery sack, shopping bag

Item	Measuring Method	Unit	Value
<b>Physical</b>			
Melt Flow Index	ASTM D1238	g/10min	0.06
Density	ASTM D1505	g/cm <sup>3</sup>	0.954
<b>Mechanical</b>			
Tensile Stress (Yield)	ASTM D638	kgf/cm <sup>2</sup>	240
Elongation (Break)	ASTM D638	%	≥500
Flexural Modulus	ASTM D790	kgf/cm <sup>2</sup>	10,000
<b>Impact</b>			
Izod Impact Strength(notched) (23°C)	ASTM D256	kgf·cm/cm	>30
<b>Thermal</b>			
VICAT Softening Temperature	ASTM D1525	°C	124
<b>Film Properties<sup>2</sup></b>			
Tensile Stress (Break) MD	ASTM D882	kgf/cm <sup>2</sup>	650
TD	ASTM D882	kgf/cm <sup>2</sup>	600
Elongation (Break) MD	ASTM D882	%	300
TD	ASTM D882	%	500
Tear Resistance MD	ASTM D1004	kgf/cm	130
TD	ASTM D1004	kgf/cm	230

1. Physical Properties : these are not to be construed as specifications
2. Φ50mm Extruder, 20 $\mu$ m Thickness, BUR 4, FLH 10

\* The last update date : 2021/10/01